



569.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Intel Tiger Lake-UP3 !
- 3x USB-C !
- 2x LAN !
- NUC Format !

- Intel® 11th Gen. Tiger Lake-UP3 SoC Processor
- 2\* DDR4 3200MHz SO-DIMM up to 64GB
- Rich and complete connection interface
- supports 4 sets of 4K HDR output
- 3\* internal M.2 expansion slots for various applications

|                |                                                                                                                                                                                                            |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model          | – N11-1115 (CPU : 1115G4)<br>– N11-1135 (CPU : 1135G7)                                                                                                                                                     |
| CPU/Chipset    | – Intel® Tiger Lake-UP3 Processor                                                                                                                                                                          |
| BIOS           | – AMI Flash ROM                                                                                                                                                                                            |
| Memory         | – 2* DDR4 3200MHz up to 64GB                                                                                                                                                                               |
| Network        | – 1* Intel i219-LM GbE<br>– 1* Intel i225-V 2.5GbE                                                                                                                                                         |
| Graphics       | – Intel® UHD / Iris Xe Graphics, shared memory<br>– 2* HDMI 2.0b (Max Resolution: 4096×2160@60Hz)<br>– 2* DP1.4 (Max Resolution: 4096×2304@60Hz) from Type-C<br>– Support Four independent 4K HDR Displays |
| Storage        | – 1* M.2 M-key 2242/2280 (PCIe4.0 x4/SATAIII interface) support NVMe<br>– 1* 2.5" SATA Device ( <a href="#">support 2.5" HDD with a height ≤ 10mm</a> )                                                    |
| Expansion slot | – 1* M.2 E Key 2230 for WiFi module<br>– 1* M.2 B Key 3042/3052 for 4G/5G module                                                                                                                           |

|                    |                                                                                                                                                                                                                   |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rear Panel I/O     | <ul style="list-style-type: none"> <li>– 2* USB3.2 (Gen.2) Type-C support DP1.4 display output</li> <li>– 1* SIM Card slot</li> <li>– 2* HDMI 2.0</li> <li>– 2* RJ45</li> <li>– 1* DC Jack</li> </ul>             |
| Front Panel I/O    | <ul style="list-style-type: none"> <li>– 1* Audio (Line out +MIC combo)</li> <li>– 2* USB3.2 / A type (Gen.2)</li> <li>– 1* USB3.2 / C type (Gen.2)</li> <li>– 1* Power Button</li> <li>– 1* Power LED</li> </ul> |
| Internal Connector | <ul style="list-style-type: none"> <li>– 1* SATAIII</li> <li>– 1* AT/ATX mode jumper</li> <li>– Onboard TPM2.0 (option)</li> </ul>                                                                                |
| Compliance         | – CE, FCC, RoHS, ErP Ready                                                                                                                                                                                        |
| Power Source       | <ul style="list-style-type: none"> <li>– MB : DC12~24V input</li> <li>– Adapter : DC12V_90W</li> </ul>                                                                                                            |
| Compliance         | – CE, FCC, LVD, RoHS                                                                                                                                                                                              |
| Temperature        | <ul style="list-style-type: none"> <li>– Operating Temperature: -10 ~ 50° C</li> <li>– Storage Temperature: -20 ~ 60° C</li> </ul>                                                                                |
| Dimensions         | <ul style="list-style-type: none"> <li>– System: 121 (W) x 113.4 (D) x 59 (H) mm</li> <li>– Box: 244 (W) x 183 (D) x 118 (H) mm</li> </ul>                                                                        |
| OS Support         | – Windows 11, Linux                                                                                                                                                                                               |
|                    |                                                                                                                                                                                                                   |